



## Park County Environmental Health

414 E. Callender

Livingston, MT 59047

Office 406-222-4145

Fax 406-222-4109

### Finish Schedule

The following chart and footnotes provide acceptable finishes for floors, walls, and ceilings by area:

	Floor	Wall	Ceiling
<u>Kitchen Cooking Area</u>	Quarry tile, poured seamless, sealed concrete	Tile, Stainless steel, aluminum	Plastic coated or metal clad fiberboard, drywall with epoxy, glazed surface, plastic laminate
<u>Kitchen Food Prep</u>	Same as above plus commercial grade vinyl composition tile	Same as above plus approved wall panels (FRP*), epoxy painted drywall, filled block & epoxy painted glazed surface	Same as above
<u>Bar</u>	Same as above	Same as above for areas behind sinks	Meets building codes
<u>Food Storage</u>	Same as above plus sealed concrete, commercial grade vinyl composition tile or sheets	Approved wall panels (FRP*); epoxy painted drywall; filled block & epoxy painted; glazed surface	Acoustic tile; painted sheetrock
<u>Toilet Room</u>	Quarry tile, poured sealed concrete; commercial grade vinyl composition tile or sheets	Approved wall panels (FRP*); epoxy painted drywall; filled block & epoxy painted; glazed surface	Plastic coated or metal clad fiberboard; drywall with epoxy; glazed surface; plastic laminate
<u>Dressing Rooms</u>	Same as above	Painted Sheetrock	Same as above plus painted sheetrock
<u>Garbage &amp; Refuse Areas (Interior)</u>	Quarry tile; poured seamless, sealed concrete; commercial grade	Approved wall panels (FRP*); epoxy painted drywall; filled block	Plastic coated or metal clad fiberboard; drywall with epoxy; glazed

<u>Garbage &amp; Refuse Areas (Interior) cont.</u>	vinyl composition tile or sheets	& epoxy painted; glazed surface	surface; plastic laminate
<u>Mop Service</u>	Quarry tile; poured seamless sealed concrete	Same as above	Same as above
<u>Ware washing Area</u>	Same as above plus commercial grade vinyl composition tile	Stainless steel; aluminum; approved wall panels (FRP*); epoxy painted drywall; filled block & epoxy painted; glazed surface	Same as above
<u>Walk-In Refrigerators &amp; Freezers</u>	Quarry tile; aluminum; stainless steel; poured sealed concrete	Aluminum; stainless steel	Aluminum; stainless steel

\*FRP = Fiberglass Reinforced Polyester Panel

- ✘ There must be coving at base junctures that is compatible to both wall and floor coverings; recommended to provide at least ¼ inch radius and 4” in height.
- ✘ All floor coverings in food prep, food storage, utensil-washing areas, walk-in refrigeration units, dressing rooms, locker rooms, toilet rooms and vestibules must be smooth, non-absorbent, easily cleanable and durable. Anti-slip floor covering may be used in high traffic areas.
- ✘ Any alternate materials not listed in the above chart must be submitted for evaluation.