



PARK CITY-COUNTY ENVIRONMENTAL HEALTH

414 East Callender Street, Livingston, MT 59047
406-222-4145 parkcounty.org

Finish Schedule

The following chart and notes explains acceptable finishes for floors, walls, and ceilings by area:

	Floors	Walls	Ceilings
Kitchen Cooking	Quarry tile, poured seamless, sealed concrete	Tile, Stainless steel, aluminum	Plastic coated or metal clad fiberboard, drywall with epoxy, glazed surface, plastic laminate
Kitchen Food Prep	Same as above plus commercial grade vinyl composition tile	Same as above plus approved wall panels (FRP*), epoxy painted drywall, filled block & epoxy painted glazed surface	Same as above
Bar	Same as above	Same as above for areas behind sinks	Meets building codes
Food Storage	Same as above plus sealed concrete, commercial grade vinyl composition tile or sheets	Approved wall panels (FRP*); epoxy painted drywall; filled block & epoxy painted; glazed surface	Acoustic tile; painted sheetrock
Toilet Room	Quarry tile, poured sealed concrete; commercial grade vinyl composition tile or sheets	Approved wall panels (FRP*); epoxy painted drywall; filled block & epoxy painted; glazed surface	Plastic coated or metal clad fiberboard; drywall with epoxy; glazed surface; plastic laminate
Dressing Rooms	Same as above	Painted Sheetrock	Same as above plus painted sheetrock
Garbage Area (Interior)	Quarry tile; poured seamless, sealed concrete; commercial grade vinyl composition tile or sheets	Approved wall panels (FRP*); epoxy painted drywall; filled block & epoxy painted; glazed surface	Plastic coated or metal clad fiberboard; drywall with epoxy; glazed surface; plastic laminate

Mop Service	Quarry tile; poured seamless sealed concrete	Same as above	Same as above
Ware-washing Area	Same as above plus commercial grade vinyl composition tile	Stainless steel; aluminum; approved wall panels (FRP*); epoxy painted drywall; filled block & epoxy painted; glazed surface	Same as above
Walk-In Freezers & Refrigerators	Quarry tile; aluminum; stainless steel; poured sealed concrete	Aluminum; stainless steel	Aluminum; stainless steel

*FRP = Fiberglass Reinforced Plastic Panels

There must be coving at base junctures that is compatible to both wall and floor coverings; recommended to provide at least ¼ inch radius and 4” in height.

All floor coverings in food prep, food storage, utensil-washing areas, walk-in refrigeration units, dressing rooms, locker rooms, toilet rooms and vestibules must be smooth, non-absorbent, easily cleanable and durable. Anti-slip floor covering may be used in high traffic areas.

Any alternate materials not listed in the above chart must be submitted for evaluation.